



SmartTest 50 Semi-Automatic Tablet Testing System

- Precise measuring of up to 5 parameters
- Reliable orientation of all tablet shapes
- Fast and intuitive touch screen operation
- Professional reporting including statistics



SmartTest 50

The SmartTest 50 sets new standards in fast and efficient semi-automatic testing of up to five physical parameters. Weight, thickness, width, diameter/length and hardness of virtually all tablet shapes can be tested in full compliance with current Pharmacopeia requirements. Proven Dr. Schleuniger® hardness measuring technology guarantees accurate and highly reliable test data that can be evaluated immediately. An integrated color touch screen with simple icon-based navigation makes operating the SmartTest 50 very intuitive consequently reducing operator training time to an absolute minimum. Perfectly suited for both laboratory and production environments, the SmartTest 50 has been designed to optimize efficiency of your quality control process without limiting the range of possible applications.




→ SmartTest 50
Semi-automatic tablet testing system

Smart, Smarter, SmartTest 50

The SmartTest 50 is capable of testing virtually all tablet shapes and can easily be programmed to meet your individual testing requirements. Tablet samples are placed in a feeder carousel by the operator and all further testing is done automatically. The patented SmartAlign™ system guarantees reliable orientation of samples in the integrated measuring stations and automatically turns both oblong and oval shapes for width and length measuring prior to hardness testing.

Especially when it comes to testing oval, oblong or other shapes, the SmartTest 50 combines maximum flexibility with reliable tablet orientation for high precision results. The integrated single-flap SmartAlign™ system ensures correct positioning of test samples at all times. As a standard, the SmartTest 50 first measures the width of tablets and then quickly re-positions them for precise length and hardness measuring – all in the same integrated measuring station. If width measuring is not required, tablets are immediately oriented for combined diameter (length) and hardness measurement.

After each measurement, an integrated cleaning function removes debris and broken tablet fragments from all contact surfaces of the hardness station for trouble-free operation. Short cycle times are maintained at all times. To «future-proof» your investment, the SmartAlign™ system does not limit the application range of the SmartTest 50 in any way. From small to large tablet sizes – almost all shapes can be tested in standard configuration. When equipped with a custom feeder carousel, there are no limits for testing even the most complex special tablet shapes.



→ Semi-automatic testing of virtually all tablet shapes and sizes with the SmartTest 50



→ SmartAlign™ to measure diameter & hardness



→ SmartAlign™ to measure width



→ SmartAlign™ to measure length & hardness



→ Top view of SmartTest 50

A: Integrated balance (depending on model)

B: Thickness measuring station

C: Width/Length (Diameter)/Hardness measuring station
with integrated SmartAlign™ system

Flexibility and Precision

Accommodating for most standard testing needs, up to 23 tablet samples are measured in one test run. If testing larger sample sizes is required, results from several test runs can be combined in a single test report – with the push of a button.

Only the combination of quality components, state-of-the-art electronics and correct tablet orientation provides test results you can rely on. The SmartTest 50 with proven Dr. Schleuniger® Pharmatron measuring technology complies with all current USP and EP requirements and offers consistently accurate results. Tablet hardness is measured using a precision S-beam load cell with a line-

arity of 99.95% over the entire measuring range. Featuring innovative light-weight construction, the integrated thickness gauge is extremely precise and applies only minimal pressure on tested tablets. To ensure stable test conditions – particularly for the integrated balance – the SmartTest 50 can be equipped with an anti-static safety cover protecting all measuring stations.

User-friendliness

Operating a semi-automatic tablet testing system has never been easier. The intuitive icon-based touch screen user interface sets new standards for fast and user-friendly control. Three test modes allow using the SmartTest 50 according to individual reporting requirements.

From executing simple tests to programming products with T1/T2/PL limits and methods – everything is configurable using the touch screen menu. Intuitive icon-based navigation and logical menu structures with intelligent operator assistance provide for fast test setup, short training time and error-free data entry.

Different views can be selected while test runs are executed, allowing the operator to display currently measured value, complete series of measurements and even graphical hardness curves. Professional reports are automatically printed at completion of a test run.

For paperless reporting and central data management in full compliance with 21 CFR, Part 11 requirements, the SmartTest 50 can be networked with the TabStat™ DataCenter.

“FullTest” mode

All product and method specifications can be pre-programmed and easily retrieved for fast test setup. Up to 100 products including nominal values and T1/T2/PL limits for all test parameters are conveniently stored directly on the SmartTest 50. On completion of each test run, a comprehensive report is printed automatically. The report shows all product and test parameters, calibration data and individually measured values along with statistical analysis.

“EasyTest” mode

For tests without T1/T2/PL limits, the “EasyTest” mode allows fast and uncomplicated setting of the desired sample size for each parameter. No programming of product specifications is required. The same reporting functions as in the “FullTest” mode are available.

“SingleTest” mode

To quickly measure single tablets without printing a report, simply activate the parameter(s) you would like to test and press start.

PC Software

All SmartTest 50 tablet testers can be connected with PC software for 21 CFR, Part 11 compliant electronic data management. Measured results and test reports are collected in a database and can be exported either as PDF or in Microsoft Excel® compatible format.







Models

The SmartTest 50 with external balance interface (instead of being equipped with an integrated weighing module) has been designed for alternative testing requirements.

The operator first measures the weight of samples individually on a connected external balance and then places them in the SmartTest 50 feeder carousel. Measured results are automatically transferred to the tester. As soon as the required sample size has been reached, testing of thickness, width, diameter/length and hardness parameters proceeds automatically. Upon completion of the test, a report with all results – including manually measured weight values – is automatically generated.



→ TDH version, connected to external balance



→ Example: TabStat™ DataManager with 2 x SmartTest 50 (TDH version and WTDH version)

Technical Specifications

SmartTest 50, Tablet testing system

Weight	Measuring range	Up to 50 g
	Resolution	0.1 mg
	Units of measure	mg/g
	Type of external balance	MettlerToledo®, Sartorius® (applies to TDH version only)
	Type of integrated balance	Sartorius® weighing module (applies to WTDH version only)
Thickness	Measuring range	Up to 15 mm (0.59 inch)
	Resolution	0.01 mm (0.00039 inch)
	Units of measure	mm / inch
Diameter / Length / Width	Measuring range	Up to 25 mm (0.98 inch)
	Resolution	0.01 mm (0.00039 inch)
	Units of measure	mm / inch
Hardness	Measuring range	Up to 800 N
	Accuracy	Better than +/- 1 N
	Units of measure	N, Sc, Kp, programmable user-defined factor (based on N)
Hardness measuring principle	Constant speed	Up to 5 mm/sec, programmable
	Linear force increase	Up to 200 N/sec, programmable
Program capacity	100 products / 20 methods	
Interfaces	Ethernet, USB, RS232	
Printer type	PostScript® network printer (LAN), PostScript® USB printer, serial printer	
Power supply	100–230 V, 50–60 Hz	
CE Conformity	All SmartTest 50 versions fully comply with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.	

		TDH	WTDH
Configuration	Hardness	●	●
	Diameter/Length	●	●
	Width	●	●
	Thickness	●	●
	Weight (integrated)	—	●
	Weight (external)	●	—
	Safety cover	○	●
Weight	(without packaging)	approx. 30 kg (66.5 lbs)	approx. 32 kg (70.5 lbs)
	Dimensions		
	Width	395 mm (15.6 inch)	395 mm (15.6 inch)
	Height	256 mm (10.1 inch)	260 mm (10.3 inch)
	Depth	505 mm (19.9 inch)	505 mm (19.9 inch)
Software	q-doc prolab®	○	○
	TabStat™ DataManager	○	○

● included ○ optional — not available

Technical specifications are subject to change without prior notice. Products illustrated in this brochure may include options or modifications not fitted as standard. No liability for errors and omissions.



Dr. Schleuniger® Pharmatron is a brand of the SOTAX Group

SOTAX Corporation | 2400 Computer Drive | Westborough, MA 01581 | USA
P +1 508 417 1112 | +1 508 616 6984 | sotaxusa@sotax.com

www.pharmatron.com

Your local sales & service partner